

# Wall mounted unit

ATXC-B + ARXC-B



Energy saving during standby mode



Online controller via app

## Siesta wall mounted unit, offering good value for money

- › Flat, stylish front panel blends easily within any interior décor and is easier to clean
- › Online controller (optional): control your indoor from any location with an app, via your local network or internet and keep an overview on your energy consumption
- › Whisper quiet in operation down to 20 dBA
- › Seasonal efficiency values up to A++ in cooling
- › Choosing for an R-32 product, reduces the environmental impact with 68% compared to R-410A and leads directly to lower energy consumption thanks to its high energy efficiency

# ATXC-B + ARXC-B




Efficiency data		ATXC + ARXC	20B + 20B	25B + 25B	35B + 35B	50B + 50B	60B + 60B	71B + 71B
Cooling capacity	Min./Max.	kW	1.3/3.0		1.3/4.0	1.4/6.2	1.8/7.0	2.3/7.3
Heating capacity	Min./Max.	kW	1.30/4.00		1.30/4.80	1.36/6.60	1.48/8.00	2.30/9.00
Power input	Cooling	Min./Nom./Max.	0.30/0.600/1.15	0.30/0.775/1.15	0.32/1.06/1.74	0.30/1.57/2.11	0.38/1.92/2.05	0.44/2.41/2.54
	Heating	Min./Nom./Max.	0.28/0.670/1.35	0.28/0.755/1.35	0.28/1.08/1.57	0.27/1.52/1.85	0.33/1.73/2.35	0.50/2.49/2.74
Space cooling	Energy efficiency class		A++					A
	Capacity	Pdesign	kW	2.08	2.57	3.44	5.08	6.21
	SEER		kW	6.81	6.74	6.78	6.40	6.38
	Annual energy consumption	kWh/a	107	133	178	278	341	464
Space heating (Average climate)	Energy efficiency class		A+					A
	Capacity	Pdesign	kW	1.87	2.23	2.24	3.90	4.10
	SCOP/A		kW	4.39	4.41	4.26	4.37	4.19
	Annual energy consumption	kWh/a	595	707	736	1,250	1,373	2,334
Nominal efficiency	EER		3.33	3.30			3.25	2.95
	COP		3.73	3.76	3.72		3.71	3.21
	Energy labeling Directive	Cooling/Heating	A/A					C/C

Indoor unit		ATXC	20B	25B	35B	50B	60B	71B	
Dimensions	Unit	HeightxWidthxDepth	288x785x250				297x1,010x288		
Weight	Unit	kg	9.00		9.50		13.0		
Air filter	Type		Removable / washable						
Fan	Air flow rate	Cooling	5.4/6.5/9/10.8			7.4/8.2/10/12.2		10.2/13.6/16/20.4	
Sound power level	Cooling		54		55		60		
	Sound pressure level	Cooling	20/26/38		21/26/39		29/33/45		
Control systems	Infrared remote control		BRC52B66						
	Wired remote control		-						
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240						

Outdoor unit		ARXC	20B	25B	35B	50B	60B	71B	
Dimensions	Unit	HeightxWidthxDepth	550x658x273			615x845x300		695x930x350	
Weight	Unit	kg	24.0		26.0		39.0		
Sound power level	Cooling		58		60		66		
Sound pressure level	Cooling	High	45		46		54		
Operation range	Cooling	Ambient	Min.-Max.			10~-46		-10~-46	
	Heating	Ambient	Min.-Max.			-15~-18			
Refrigerant	Type		R-32						
	GWP		675.0						
	Charge	kg/TCO2Eq	0.550/0.371		0.750/0.506		1.00/0.675		
Piping connections	Liquid	OD	mm		64				
	Gas	OD	mm				12.7		
	Piping length	OU - IU	Max.	m		20		30	
	Additional refrigerant charge	System	Chargeless	m		8			
	Level difference	IU - OU	Max.	m		15.0		20.0	
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240						
Current - 50Hz	Maximum fuse amps (MFA)	A	16				20		

Daikin Europe N.V. · goliat.d@daikineurope.com · 0 0 · Poland · 0 · 0 · 0 (Responsible Editor)



ECPEN19-054

03/2019

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this publication to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.

