



## Wall mounted unit

ATXC-C / ARXC-C

BLUEEVOLUTION

*Siesta*



Energy saving during standby mode



Online controller via app

Siesta wall mounted unit, offering good value for money

- › Flat, stylish front panel blends easily with any interior décor and is easier to clean
- › Online controller (optional)
- › Whisper quiet

- › Seasonal efficiency values up to A++ in cooling
- › Bluevolution range: lower environmental impact

# ATXC-C / ARXC-C



ATXC-C




ARXC20-35C

Efficiency data		ATXC + ARXC	20C + 20C	25C + 25C	35C + 35C	50C + 50C	60C + 60C	71C + 71C	
Cooling capacity	Min./Max.	kW	1.3 / 3.0		1.3 / 4.0	1.4 / 6.2	1.8 / 7.0	2.3 / 7.3	
Heating capacity	Min./Max.	kW	1.30 / 4.00		1.30 / 4.80	1.36 / 6.60	1.48 / 8.00	2.30 / 9.00	
Space cooling	Energy efficiency class		A++						
	Capacity	Pdesign	kW	2.08	2.57	3.44	5.08	6.21	6.96
	SEER			6.81	6.74	6.78	6.40	6.38	5.25
	Annual energy consumption		kWh/a	107	133	178	278	341	464
Space heating (Average climate)	Energy efficiency class		A+						
	Capacity	Pdesign	kW	1.87	2.23	2.24	3.90	4.10	6.35
	SCOP/A			4.39	4.41	4.26	4.37	4.19	3.81
	ηs,h		%	-					
Annual energy consumption		kWh/a	595	707	736	1,250	1,373	2,334	

Indoor unit		ATXC	20C	25C	35C	50C	60C	71C		
Dimensions	Unit	HeightxWidthxDepth	mm			288 x770 x234		297 x990 x273		
Weight	Unit		kg		9.00		9.50		13.0	
Air filter	Type		Removable / washable							
Fan	Air flow rate	Cooling	m <sup>3</sup> /min			5.4 / 6.5 / 9 / 10.8		7.4 / 8.2 / 10 / 12.2		10.2 / 13.6 / 16 / 20.4
		Silent operation/Low/Medium/High								
Sound power level	Cooling		dBA		54		55		57	60
Sound pressure level	Cooling	Silent operation/Low/High	dBA		20 / 26 / 38		21 / 26 / 39		29 / 33 / 45	30 / 38 / 46
Control systems	Infrared remote control		ARC486A2							

Outdoor unit		ARXC	20C	25C	35C	50C	60C	71C			
Dimensions	Unit	HeightxWidthxDepth	mm			550 x658 x273		615 x845 x300		695 x930 x350	
Weight	Unit		kg		24.0		26.0		39.0	45.0	
Sound power level	Cooling		dBA		58		60		65	66	69
Sound pressure level	Cooling	High	dBA		45		46		51	54	
Operation range	Cooling	Ambient	Min.-Max.	°CDB		10 ~46		-10 ~46			
	Heating	Ambient	Min.-Max.	°CWB		-15 ~18					
Refrigerant	Type	R-32									
	GWP	675.0									
	Charge	kg/TCO2Eq	0.550 / 0.371		0.750 / 0.506		1.00 / 0.675		1.10 / 0.743		1.15 / 0.776
Piping connections	Liquid	OD	mm		6.4						
	Gas	OD	mm		9.52		12.7				
	Piping length	OU - IU	Max.	m		20		30			
		System	Chargeless	m		8					
	Additional refrigerant charge	IU - OU		Max.	m		15.0		20.0		
Power supply	Phase/Frequency/Voltage		Hz/V		1~/50 / 220-240						
Current - 50Hz	Maximum fuse amps (MFA)		A		16						

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · BE 0412 120 336 (Responsible Editor)



Daikin Europe N.V. participates in the Eurovent Certified Performance programme for Fan Coil Units and Variable Refrigerant Flow systems. Check ongoing validity of certificate: www.eurovent-certification.com

ECPEN21-054

12/2020



The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. / Daikin Central Europe HandelsGmbH. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH have compiled the content of this publication to the best of their knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.